

Mini multiple trimless for smartrings 1x LED GE

125350XX-B1_125351X-B1X_125352XX-B1

1

Has to be combined with :
10460130 Mini-multiple trimless 1 recessed frame

hole dimension for recessed frame.
134.5x107mm

ELECTRICAL SPECS LED-FIXTURE			
Drive Current (mA)	Forward Voltage		Power (W)
	min (Vf)	max (Vf)	
350	13,2	15,0	5,0
500	13,7	15,4	7,2

+ RED **-** BLACK

For serial connection, respect polarity!
Not suited for connection to mains voltage.
Combine with a Modular LED-driver.

250 x 250 mm

120 mm

115 mm

Min. 1mm
max. 25mm

2

11mm

0,2 - 4mm²
24 - 12 AWG

driver - + driver

driver - + driver

DO NOT TOUCH LED

OFF

3

driver - + driver

driver - + driver

DO NOT TOUCH REFLECTOR

Frontring Smart flatring:
Turn

Frontring Smart kup-Cake-Lotis ring:
Push

4

ON

LIGHT SOURCE - DO NOT TOUCH LED

Touching the LED can result in permanent damage of the light source. The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.

PREVENTING ELECTROSTATIC DAMAGE

A discharge of static electricity may damage sensitive components. Therefore do not touch the LED nor the stripped parts of the wires with bare hands. Always be properly insulated by using ESD gloves.

DRIVERS & ACCESSORIES

For latest version of driver matrix and available accessories check www.supermodular.com or connect with your sales contact.