



## BOXY XL R C 93037 B-B



251 73 21 933 B-B

AVAILABLE IN

**BLACK-BLACK** 251 73 21 933 B-B

**WHITE-BLACK** 251 73 21 933 W-B

**WHITE-WHITE** 251 73 21 933 W-W



[View on website](#)

### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Suspended
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	1.8
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	REFLECTOR FL-37° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC INCL.1 x CABLE SUSPENSION SINGLE AUTO. 1.6m INCL.1 x CABLE 2 x 0,75mm <sup>2</sup>

### Electrical info

<b>ELECTRICAL</b>	220-240V / 50-60Hz
<b>CLASS</b>	I
<b>POWER SUPPLY INCLUDED</b>	YES
<b>DIM TYPE</b>	mains (phase cut-off)
<b>ENERGY CLASS</b>	C
<b>CERTIFICATES</b>	ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 16,3W / CRI>90 (R9: 52) / 3000K / 2309lm
<b>TM-30 VALUES</b>	Rf: 90 / Rg: 99
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>LED TECHNICS (LIGHT SOURCE)</b>	2309lm // 16,3W // 142lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	2058lm // 19W // 110lm/W

### Options

COVERSET R 90-100  
SUSPENSION + CONNECTION TRIMLESS

### Accessories

HONEYCOMB 78  
SOFTENING LENS 78

CLASS SBL 78

 DELTALIGHT®

**BOXY XL R C 93037 B-B**

251 73 21 933 B-B

For detailed installation instructions, please consult the manual: [251\\_73\\_21\\_XXX\\_HAND.pdf](#)


## BOXY XL R C 93037 B-B

251 73 21 933 B-B

### FINISH YOUR SPECIFICATION

#### Control gear, ballast and transformers


---



**300 90 004 ED8** WIRELESS CONTROL DIM8

#### Coversets

---




**204 00 100 B** COVERSET R 100 B

**204 00 100 W** COVERSET R 100 W

#### Suspension parts

---




**328 10 02** SUSPENSION + CONNECTION TRIMLESS O.F.A.

**BOXY XL R C 93037 B-B**

251 73 21 933 B-B

**Light altering devices**

---



**201 02 01 B** HONEYCOMB 78 B

Ø78



**201 02 04** SOFTENING LENS 78

Ø78



**201 02 05** GLASS SBL 78

Ø78

Notes: