





## ENTERO RD-M X TW 96518 B

28445 9010 B

AVAILABLE IN  
**BLACK** 28445 9010 B  
**FLEMISH BRONZE OUTDOOR** 28445 9010 FBRX  
**ANTHRACITE (DARK GREY)** 28445 9010 N  
**WHITE** 28445 9010 W



 [View on website](#)

### General info

<b>LOCATION</b>	outdoor
<b>INSTALLATION</b>	Ceiling Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	round - 92
<b>RECESSED DEPTH (MM)</b>	140
<b>THICKNESS OF MOUNTING SURFACE (MM)</b>	max.16
<b>INGRESS PROTECTION</b>	IP65
<b>PROTECTION AGAINST MECHANICAL IMPACT</b>	IK06
<b>WEIGHT (KG)</b>	0.46
<b>ADJUSTABILITY</b>	0° to 20° swiveling, 355° rotatable
<b>INFORMATION</b>	REFLECTOR SP-18° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on type of external power supply
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
<b>TM-30 VALUES</b>	Rf: 89 / Rg: 100
<b>SDCM</b>	SDCM2
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>LED TECHNICS (LIGHT SOURCE)</b>	1087lm // 9W // 121lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	660lm // 10W // 64lm/W

### Requirements

LED POWER SUPPLY 500mA-DC TW

### Options

ENTERO RD-M MOUNTING SET S2

## ENTERO RD-M X TW 96518 B













28445 9010 B

### Accessories

ENTERO M HONEYCOMB  
 ENTERO M LINEAR SPREAD LENS  
 ENTERO M SPREAD LENS  
 ENTERO M SOFTENING LENS  
 ENTERO M GLASS SBL

For detailed installation instructions, please consult the manual: [28445\\_XXXO\\_HAND.pdf](#)

## CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	 ENTERO RD-M MOUNTING SET S2 <span style="float: right;">Required</span>
 Concrete + plaster	 ENTERO RD-M MOUNTING SET S2 <span style="float: right;">Required</span>
 Lintel + plaster	 ENTERO RD-M MOUNTING SET S2 <span style="float: right;">Required</span>
 Hollow-core slab	 ENTERO RD-M MOUNTING SET S2 <span style="float: right;">Required</span>
 Hollow-core slab + plaster	 ENTERO RD-M MOUNTING SET S2 <span style="float: right;">Required</span>
 Stretched ceiling	-


# ENTERO RD-M X TW 96518 B

28445 9010 B

## FINISH YOUR SPECIFICATION

### LED power supplies


#




**21012 0355** LED POWER SUPPLY 500mA-DC 2CH TW DIM5

1->2


### Light altering devices




**28500 0070** ENTERO M LINEAR SPREAD LENS




**28500 0080** ENTERO M SPREAD LENS



**28500 0090** ENTERO M SOFTENING LENS




**28500 0100** ENTERO M GLASS SBL



**28500 0110 B** ENTERO M HONEYCOMB SINGLE USE B

### Mounting set S2



**28500 0200** ENTERO RD-M MOUNTING SET S2



# **ENTERO RD-M X TW 96518 B**

28445 9010 B

Notes: